

# WINTER COVER LIMITED WARRANTY

COVERTECH INDUSTRIES LTD., at its sole discretion, warrants the original purchaser of said winter cover that the company at its option, will repair or replace any winter cover that proves to be defective in workmanship or material. Winter covers returned that reveal damage from abuse or neglect are void under the warranty. Covertech Industries will not be liable for any incidental damage. Prior to storing cover it is necessary to apply a lubricant on bead to prevent shrinkage. Bead shrinkage voids the warranty.



## 10 - Season Limited Warranty, 2-Season Full

COVERTECH INDUSTRIES warrants the winter cover will be free of defects in material and may be repaired or replaced at the company's option within 2 seasons of the cover purchase date. Freight and applicable taxes extra.

3rd year replacement charge	- 50% of suggested list price
4th year replacement charge	- 60% of suggested list price
5th year replacement charge	- 70% of suggested list price
6th year replacement charge	- 75% of suggested list price
7th year replacement charge	- 80% of suggested list price
8th year replacement charge	- 85% of suggested list price
9th year replacement charge	- 90% of suggested list price
10th year replacement charge	- 95% of suggested list price

### WARRANTY CLAIM REQUIREMENTS

- Cover must be returned to manufacturer - customer to pay freight.
- Covers returned for repair must be clean and dry. Dirty covers will not be repaired or replaced under warranty.
- Attach a return address and phone number with proof of purchase to the returned cover.
- Must specify the problem with the cover and its location. If possible, please provide a sketch.
- Upon receipt, you must allow 8-10 weeks for the cover to be repaired.

**DO NOT RETURN YOUR BLANKET TO DEALER**

THE FOLLOWING ARE SPECIFICALLY EXCLUDED FROM THE PRODUCT WARRANTY (ORDINARY WEAR AND TEAR, DAMAGE CAUSED BY ANIMALS AND RODENTS) COVERTECH INDUSTRIES LIMITED WILL NOT BE LIABLE FOR ANY INCIDENTAL DAMAGE.

All Warranty Claims must be requested directly from Covertech Industries Limited

All freight charges and taxes are the responsibility of the claimant.

For more information, contact the customer service team at

[info@covertechind.com](mailto:info@covertechind.com)

Or consult the company website:

[www.covertechind.com](http://www.covertechind.com)



**WARNING**

**AVOID DROWNING RISK**

- STAY OFF COVER, DOES NOT SUPPORT WEIGHT.
- KEEP CHILDREN AWAY. CHILDREN OR OBJECTS CANNOT BE SEEN UNDER COVER.
- REMOVE STANDING WATER - CHILD CAN DROWN ON TOP OF COVER.
- REMOVE COVER(S) COMPLETELY BEFORE ENTRY - ENTRAPMENT POSSIBLE.
- NON-SECURED OR IMPROPERLY SECURED COVERS ARE A HAZARD.
- FAILURE TO FOLLOW ALL INSTRUCTIONS MAY RESULT IN INJURY OR DROWNING.
- THIS IS NOT A SAFETY COVER

**REGISTER WARRANTY ONLINE AT [WWW.COVERTECHIND.COM](http://WWW.COVERTECHIND.COM)**



COVERTECH INDUSTRIES LIMITED

26 Dansk Court, Toronto, ON M9W 5V8 Tel. (416) 640-5590

[info@covertechind.com](mailto:info@covertechind.com) / [www.covertechind.com](http://www.covertechind.com)

03/21/2024

# WINTER COVER (BEADED) INSTALLATION AND STORAGE INSTRUCTIONS

## GENERAL PREPARATIONS

- Drop water level to pool manufactures recommendation.
- Remove ladders, pool cleaner and obstructions from the pool.
- Confirm water is, balanced, free of algae and winterizing chemicals are added.
- Remove directional eyeball and insert proper size winter plug.
- Drain filter, pump, pipes, and hoses of water. Follow pump and filter manufacturer's Instructions for winterizing.
- Skimmer: Remove basket and weir. Insert Gizzmo and/or winterizing plate to prevent Ice from forming a solid block that could damage your skimmer. If using a Gizzmo, the standard size is recommended for Above-ground skimmers. For In-ground skimmers, the super Gizzmo is recommended.

## INSTALLATION

- Install winter cover by inserting beading on cover into bead track of your coping.
- in Above-ground pools, the cover bead track on the standard 2" coping is located on the exterior of the pool. The cover bead on the 4" coping is located on the interior of the pool, above the liner track.
- Excess cover material should be inside the pool and resting on the water.
- Add a little water on the cover in windy areas to hold the cover down.
- No air pillow or flotation device is required.

## REMOVAL & STORAGE

- When removing cover apply lubricant to bead to maintain flexibility and prevent shrinkage. Warranty is void when bead is not treated and cover not cleaned properly.
- Cover should be stored in a dry area at temperature below 90° F / 32° C.

**REGISTER WARRANTY ONLINE AT [WWW.COVERTECHIND.COM](http://WWW.COVERTECHIND.COM)**



**COVERTECH INDUSTRIES LIMITED**

26 Dansk Court, Toronto, ON M9W 5V8 Tel. (416) 640-5590  
info@covertechind.com / www.covertechind.com

03/21/2024